

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 06/01/2015

Revision date: 10/17/2016

Version: 610B-2016a

### SECTION 1: Identification

#### Identification

**Product name** : WEST SYSTEM® SIX10® Part B Hardener

**Product code** : 610B

**Relevant identified uses of the substance or mixture and uses advised against**

**Recommended use** : Curing agent for epoxy resins

#### Details of the supplier of the safety data sheet

#### Manufacturer

Gougeon Brothers, Inc  
100 Patterson Ave.  
Bay City, MI 48706 - U.S.A.  
T 866-937-8797 or 989-684-7286  
[www.westsystem.com](http://www.westsystem.com)

#### Emergency telephone number

**Emergency number** : CHEMTREC 1 (800) 424-9300  
CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

Skin Corr. 1B  
Eye Dam. 1  
Skin Sens. 1  
Muta. 2  
STOT RE 2  
Aquatic Acute 3  
Aquatic Chronic 3

#### Label elements

#### Hazard pictograms (GHS)



GHS05



GHS07



GHS08

#### Signal word (GHS)

Danger

#### Hazard statements (GHS)

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects

#### Precautionary statements (GHS)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a poison center/doctor. Take off contaminated clothing and wash it before reuse. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### Other hazards

No additional information available

#### Unknown acute toxicity

Not applicable

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 3: Composition/information on ingredients

#### Substance

Not applicable

#### Mixtures

Name	Product identifier	%
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	(CAS No) 68683-29-4	10 - 40
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0	10 - 40
Benzyl alcohol	(CAS No) 100-51-6	10 - 40
Non-hazardous	(CAS No) Trade Secret	5 - 20
Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol	(CAS No) 32610-77-8	5 - 20
Triethylenetetramine	(CAS No) 112-24-3	1 - 10
Phenol, 2,4,6-tris[(dimethylamino)methyl]-, reaction products with triethylenetetramine	(CAS No) 1101788-77-5	1 - 10
Silica, amorphous, fumed, crystalline-free	(CAS No) 112945-52-5	1 - 10
Phenol	(CAS No) 108-95-2	1 - 5
1,3-Benzenedimethanamine	(CAS No) 1477-55-0	1 - 5
Diethylenetriamine-bisphenol A-epichlorohydrin polymer	(CAS No) 31326-29-1	1 - 5
Diethylenetriamine	(CAS No) 111-40-0	1 - 5

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold. Refer to Section 15 for additional information regarding this CBI claim.

### SECTION 4: First aid measures

#### Description of first aid measures

#### First-aid measures after inhalation

: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

#### First-aid measures after skin contact

: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

#### First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

#### First-aid measures after ingestion

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

#### Most important symptoms and effects, both acute and delayed

#### Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

#### Symptoms/injuries after skin contact

: Causes severe burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.

#### Symptoms/injuries after eye contact

: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

#### Symptoms/injuries after ingestion

: May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.

#### Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### Extinguishing media

#### Suitable extinguishing media

: Foam. Carbon dioxide. Dry chemical.

#### Unsuitable extinguishing media

: Do not use a heavy water stream.

#### Special hazards arising from the substance or mixture

#### Fire hazard

: Products of combustion may include, and are not limited to: oxides of carbon, oxides of nitrogen, amines, ammonia, nitric acid, aldehydes, nitrosamines. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. Heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

#### Reactivity

: No dangerous reaction known under conditions of normal use.

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### Advice for firefighters

**Protection during firefighting** : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### For non-emergency personnel

No additional information available

### For emergency responders

No additional information available

### Environmental precautions

No additional information available

### Methods and material for containment and cleaning up

**For containment** : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for cleaning up** : Scoop up material and place in a disposal container. Provide ventilation.

### Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### Precautions for safe handling

**Precautions for safe handling** : Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, vapours, spray. Do not swallow. Handle and open container with care. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

**Hygiene measures** : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### Conditions for safe storage, including any incompatibilities

**Storage conditions** : Keep out of the reach of children. Keep container tightly closed. Store in dry, cool, well-ventilated area. Protect from sunlight. Storage temperature : 40°F (4°C) - 90°F (32°C).

## SECTION 8: Exposure controls/personal protection

### Control parameters

<b>2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated (68683-29-4)</b>		
Not applicable		
<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>		
Not applicable		
<b>Benzyl alcohol (100-51-6)</b>		
WEEL	WEEL (TWA) (ppm)	10 ppm
<b>Non-hazardous (Trade Secret)</b>		
Not applicable		
<b>Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol (32610-77-8)</b>		
Not applicable		
<b>Triethylenetetramine (112-24-3)</b>		
AIHA WEEL	WEEL (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> absorbed via skin
AIHA WEEL	WEEL (ppm)	1 ppm absorbed via skin

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Phenol, 2,4,6-tris[(dimethylamino)methyl]-, reaction products with triethylenetetramine (1101788-77-5)</b>		
AIHA WEEL	WEEL (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> absorbed via skin (Reference Triethylenetetramine)
AIHA WEEL	WEEL (ppm)	1 ppm absorbed via skin
<b>Silica, amorphous, fumed, crystalline-free (112945-52-5)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable) 3 mg/m <sup>3</sup> (Respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> (Amorphous silica) 15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
<b>Phenol (108-95-2)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	19 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	5 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	19 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	5 ppm
IDLH	US IDLH (ppm)	250 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	19 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	60 mg/m <sup>3</sup>
NIOSH	NIOSH REL (ceiling) (ppm)	15.6 ppm
<b>1,3-Benzenedimethanamine (1477-55-0)</b>		
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
<b>Diethylenetriamine-bisphenol A-epichlorohydrin polymer (31326-29-1)</b>		
Not applicable		
<b>Diethylenetriamine (111-40-0)</b>		
ACGIH	ACGIH TWA (ppm)	1 ppm

### Exposure controls

#### Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

#### Hand protection

: Wear suitable gloves.

#### Eye protection

: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

#### Skin and body protection

: Wear suitable protective clothing.

#### Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Environmental exposure controls

: Maintain levels below Community environmental protection thresholds.

#### Other information

: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

#### Physical state

: Liquid

#### Appearance

: Gel

#### Colour

: Off-white

#### Odour

: Amine-like

#### Odour threshold

: No data available

#### pH

: 10.59

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Melting point</b>	: No data available
<b>Freezing point</b>	: No data available
<b>Boiling point</b>	: No data available
<b>Flash point</b>	: > 300 °F (149°C) (estimated based similar product)
<b>Relative evaporation rate (butylacetate=1)</b>	: No data available
<b>Flammability (solid, gas)</b>	: Non flammable.
<b>Vapour pressure</b>	: No data available
<b>Relative vapour density at 20 °C</b>	: No data available
<b>Relative density</b>	: 1.04
<b>Solubility</b>	: No data available
<b>Partition coefficient n-octanol/water</b>	: No data available
<b>Auto-ignition temperature</b>	: No data available
<b>Decomposition temperature</b>	: No data available
<b>Viscosity, kinematic</b>	: No data available
<b>Viscosity, dynamic</b>	: No data available
<b>Explosive limits</b>	: No data available
<b>Explosive properties</b>	: No data available
<b>Oxidising properties</b>	: No data available
<b>Other information</b>	
<b>VOC content</b>	: 11.8 g/l (0.10 lbs/gal)
<b>Bulk density</b>	: 8.67 lb/gal (1.04 kg/L)

### SECTION 10: Stability and reactivity

<b>Reactivity</b>	: No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	: Stable under normal storage conditions.
<b>Possibility of hazardous reactions</b>	: No dangerous reaction known under conditions of normal use. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure.
<b>Conditions to avoid</b>	: Heat. Ignition sources. Incompatible materials.
<b>Incompatible materials</b>	: Acids. oxidizing materials. Halogenated compounds.
<b>Hazardous decomposition products</b>	: May include, and are not limited to: oxides of carbon, oxides of nitrogen, amines, ammonia, nitric acid, aldehydes, nitrosamines.

### SECTION 11: Toxicological information

#### Information on toxicological effects

<b>2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated (68683-29-4)</b>	
LD50 oral rat	> 15400 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>	
LD50 oral rat	2855 mg/kg
LD50 dermal rabbit	2890 ml/kg
LC50 inhalation rat	> 0.74 mg/l/8h

<b>Benzyl alcohol (100-51-6)</b>	
LD50 oral rat	1620 mg/kg
LC50 inhalation rat	> 4.18 mg/l/4h

<b>Triethylenetetramine (112-24-3)</b>	
LD50 oral rat	1716 mg/kg
LD50 dermal rabbit	1465

<b>Phenol, 2,4,6-tris[(dimethylamino)methyl]-, reaction products with triethylenetetramine (1101788-77-5)</b>	
LD50 oral rat	1716 mg/kg (Reference Triethylenetetramine)
LD50 dermal rabbit	1465 mg/kg

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Silica, amorphous, fumed, crystalline-free (112945-52-5)</b>	
LD50 oral rat	> 5000 mg/kg OECD 401
LD50 dermal rabbit	> 2000 mg/kg OECD 402

<b>Phenol (108-95-2)</b>	
LD50 oral rat	317 mg/kg
LD50 dermal rabbit	630 mg/kg Solid
LC50 inhalation rat	0.9 mg/l/8h

<b>1,3-Benzenedimethanamine (1477-55-0)</b>	
LD50 oral rat	980 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat	1.34 mg/l/4h

<b>Diethylenetriamine-bisphenol A-epichlorohydrin polymer (31326-29-1)</b>	
LD50 oral rat	1620 mg/kg

<b>Diethylenetriamine (111-40-0)</b>	
LD50 oral rat	1080 mg/kg
LD50 dermal rabbit	1090 mg/kg
LC50 inhalation rat	*0.07 - 0.3 mg/l/4h (aerosol/mist)

<b>Acute toxicity (oral)</b>	: Not classified.
<b>Acute toxicity (dermal)</b>	: Not classified.
<b>Acute toxicity (inhalation)</b>	: Not classified.
<b>Skin corrosion/irritation</b>	: Causes severe skin burns.
<b>Serious eye damage/irritation</b>	: Causes serious eye damage.
<b>Respiratory or skin sensitization</b>	: May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	: Suspected of causing genetic defects.
<b>Carcinogenicity</b>	: Not classified.

\* LC50 data has been generated for this substance by subjecting rats to an airborne aerosol/mist atmosphere in a test chamber. It has not been determined that this data directly correlates to an inherent hazard of this product as would be expected under normal, foreseeable or anticipated conditions of use.

<b>Silica, amorphous, fumed, crystalline-free (112945-52-5)</b>	
IARC group	3 - Not classifiable

<b>Phenol (108-95-2)</b>	
IARC group	3 - Not classifiable

<b>Reproductive toxicity</b>	: Not classified.
<b>STOT-single exposure</b>	: Not classified.
<b>STOT-repeated exposure</b>	: May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	: Not classified.
<b>Symptoms/injuries after inhalation</b>	: May cause respiratory tract irritation.
<b>Symptoms/injuries after skin contact</b>	: Causes severe burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.
<b>Symptoms/injuries after eye contact</b>	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
<b>Symptoms/injuries after ingestion</b>	: May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.
<b>Other information</b>	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### Toxicity

**Ecology - general** : Harmful to aquatic life with long lasting effects.

<b>Benzyl alcohol (100-51-6)</b>	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Benzyl alcohol (100-51-6)</b>	
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

<b>Triethylenetetramine (112-24-3)</b>	
LC50 fish 1	570 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 Daphnia 1	31.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	495 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

<b>Phenol (108-95-2)</b>	
LC50 fish 1	11.9 - 50.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4.24 - 10.7 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	20.5 - 25.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	10.2 - 15.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

<b>Diethylenetriamine (111-40-0)</b>	
LC50 fish 1	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])

### Persistence and degradability

<b>WEST SYSTEM® SIX10® Part B Hardener</b>	
Persistence and degradability	Not established.

### Bioaccumulative potential

<b>WEST SYSTEM® SIX10® Part B Hardener</b>	
Bioaccumulative potential	Not established.

<b>Benzyl alcohol (100-51-6)</b>	
Partition coefficient n-octanol/water	1.1

<b>Triethylenetetramine (112-24-3)</b>	
BCF fish 1	(no bioaccumulation expected)
Partition coefficient n-octanol/water	-1.4

<b>Phenol (108-95-2)</b>	
BCF fish 1	(no significant bioaccumulation)
Partition coefficient n-octanol/water	1.5

<b>Diethylenetriamine (111-40-0)</b>	
BCF fish 1	0.3 - 1.7
Partition coefficient n-octanol/water	-1.3

### Mobility in soil

<b>WEST SYSTEM® SIX10® Part B Hardener</b>	
Ecology - soil	No additional information available.

### Other adverse effects

**Effect on the global warming** : No known effects from this product.

**Other information** : Avoid release to the environment.

Name	Product identifier	Ecotoxicity Classification Information
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	(CAS No) 68683-29-4	No data available
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0	Aquatic Acute Cat. 3; Aquatic Chronic Cat. 2
Benzyl alcohol	(CAS No) 100-51-6	No data available
Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol	(CAS No) 32610-77-8	Aquatic Chronic Cat. 3
Non-hazardous	(CAS No) Trade Secret	No data available
Triethylenetetramine	(CAS No) 112-24-3	Aquatic Chronic Cat. 3

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Product identifier	Ecotoxicity Classification Information
Silica, amorphous, fumed, crystalline-free	(CAS No) 112945-52-5	No data available
Phenol, 2,4,6-tris[(dimethylamino)methyl]-, reaction products with triethylenetetramine	(CAS No) 1101788-77-5	(Reference Triethylenetetramine); Aquatic Chronic Cat. 3
Phenol	(CAS No) 108-95-2	Aquatic Acute Cat. 3; Aquatic Chronic Cat. 2
Diethylenetriamine-bisphenol A-epichlorohydrin polymer	(CAS No) 31326-29-1	No data available
Diethylenetriamine	(CAS No) 111-40-0	No data available
1,3-Benzenedimethanamine	(CAS No) 1477-55-0	Aquatic Acute Cat. 3; Aquatic Chronic Cat. 3

### SECTION 13: Disposal considerations

#### Waste treatment methods

**Product/Packaging disposal recommendations** : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. Avoid release to the environment. The generation of waste should be avoided or minimized wherever possible.

### SECTION 14: Transport information

#### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT and TDG

UN-No. (DOT/TDG) : UN3259  
Proper Shipping Name (DOT/TDG) : Polyamines, solid, corrosive n.o.s.  
Class (DOT/TDG) : Class 8 - Corrosive material 49 CFR 173.136  
Packing group (DOT/TDG) : III

#### Transport by sea

In accordance with IMDG

UN-No. (IMDG) : 3259  
Proper Shipping Name (IMDG) : POLYAMINES, SOLID, CORROSIVE, N.O.S.  
Class (IMDG) : Class 8 - Corrosive substances  
Packing group (IMDG) : III

#### Transport by air

In accordance with IATA

UN-No. (IATA) : 3259  
Proper Shipping Name (IATA) : Polyamines, solid, corrosive, n.o.s.  
Class (IATA) : Class 8 - Corrosives  
Packing group (IATA) : III

### SECTION 15: Regulatory information

#### Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

<b>2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated (68683-29-4)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
<b>Formaldehyde, polymer with N,N'-bis(2-aminoethyl)-1,2-ethanediamine and phenol (32610-77-8)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).



# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Phenol, 2,4,6-tris[(dimethylamino)methyl]-, reaction products with triethylenetetramine (1101788-77-5)</b>	
EPA TSCA Regulatory Flag	P - P - indicates a commenced PMN substance.

<b>Phenol (108-95-2)</b>	
Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 - 10000 lb
SARA Section 313 - Emission Reporting	1 %

<b>Diethylenetriamine-bisphenol A-epichlorohydrin polymer (31326-29-1)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

<b>Propylene oxide (75-56-9)</b>	
Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb
SARA Section 313 - Emission Reporting	0.1 %

Canada WHMIS Confidential Business Information (CBI): The HMIRA number issued for this CBI claim is #10442. The date of filing is 2016-10-13.

### International regulations

No additional information available

### US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

<b>Propylene oxide (75-56-9)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

<b>Benzyl alcohol (100-51-6)</b>	
U.S. - Pennsylvania - RTK (Right to Know) List	

<b>Triethylenetetramine (112-24-3)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

<b>Phenol (108-95-2)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	

<b>1,3-Benzenedimethanamine (1477-55-0)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

<b>Diethylenetriamine (111-40-0)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

# WEST SYSTEM® SIX10® Part B Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015


### Propylene oxide (75-56-9)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

**Date of issue** : 06/01/2015  
**Revision date** : 10/17/2016  
**Version** : 610B-2016a  
**Other information** : None.

**NFPA health hazard** : 3  
**NFPA fire hazard** : 1  
**NFPA reactivity** : 0



**HMIS III Rating**  
**Health** : 3  
**Flammability** : 1  
**Physical** : 0

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*